


Mounting instruction for ALUPROFF roman blind system SB 3003 & SB 3004 w/velcro



The fabric is cut (remember seam allowance) and 2 cm side seams is sewn.

The Velcro tape is sewn to the top of the curtain and a 2.5 cm drawstring is sewn in the bottom, as shown in the drawing.

Pocket tape is attached with approx. 20-25 cm distance across the curtain. The weight is placed in the bottom of the lower drawstring and fiber rods entered in the pocket bands. The curtain with the Velcro strap on top, is attached to the Velcro profile.

Attach a cord eye approx. 5 cm into both ends of the profile , and for every approx. 30-40 cm . Attach the cord lock at the outside of the outer cord eye, in right or left side. Attach the small rings at the bottom, with the same distance as the cord eyes . Now the strings can be mounted.

These are tied to the rings at the bottom and be led vertically through the pockets on the tape to the cord eye, and horizontally through the other cord eyes and down through the lock between the steel wheel and the smooth plastic part. Finally the strings is led through the tassel and a knot is tied on the cord so that all the strings are of equal length . This ensures a horizontal pull-up.

Important ! :
Minimum stitch length = 2.5 mm by needle size 80
Minimum stitch length = 2.8 mm by needle size 90
Minimum stitch length = 3.0 mm by needle size 120

Important!
 When the cord collector is used with 2-4 cords, there must be one string through both the two round holes.
 When the cord collector used with 5 or 6 strings, there must be one string through both the two round holes, and 1-2 cords through the oval holes

